

PRODUCT DATA SHEET

94 Eagle Fork Rd Hayesville, NC 28904 Ph: 800.343.2579 Fax: 828.389.3922

Part Number: 18022TSD

City of Los Angeles - 18 AWG 4C (2 shielded pairs with drains) and overall shield. HDPE

Description: Insulation and Jacket which meets requirements of ASTM D 1248, Type III, Class A,

Category 5, Grade E8.

Suitable Application(s): LA DOT Loop Home-Run Cable

Construction Details:

Total Number of Conductors	4 (2 Pairs)
Conductor Material	18 AWG 7-Strand Tinned Copper
Insulation Material(s)	High-Density Polyethylene
Nom. Insulation Thickness	0.013"
Nom. Diameter over Insulation	0.072"
Conductor Insulation Color Code	Pair #1: White, Blue Pair #2: White, Orange
Shielding Tape Material (Pairs)	Aluminum / Mylar
Drain Wire Material (Pairs)	20 AWG 7-Strand Tinned Copper
Overall Shielding Material	Aluminum / Mylar Tape (No overall Drain Wire)
Nom. Cabling Overall Lay Length	3.50" Left-Hand Lay
Final Jacket Material	High-Density Polyethylene
Nom. Final Jacket Thickness	0.030"
Final Jacket Color	Black
Nominal Diameter over Final Jacket	0.265"
Ripcord	Yes

Jacket Print Details:

Type: Inkjet Sequential Foot Markings: Yes

Sample Print Legend:

ADVANCED DIGITAL CABLE, INC. 2 PAIR 18 AWG LA DOT LOOP HOME-RUN CABLE 300V YYYY

Replace "YYYY" with year of manufacture.

Applicable Standards and Ratings			
Conductor Voltage Rating	300V		
Insulation Temperature Rating	-40°C to +75°C		
City of Los Angeles Specification #	92-082-03		
UL Type(s)	N/A		
ROHS Compliant	Yes		

Customer Approval Signature:		Date:
Customer Name:		
Specification Issue Date:	04/10/2018; Revised: 11/14/2022	